EJOT® stainless steel bi-met self-drilling fasteners

JT3-FR-2H-4.8/JT3-FR-2H-6.3 x L ranges



A2 stainless steel bi-met fastener with low profile head stitching fastener.

Application Features

- · Stitching laps of steel roofing and cladding sheets
- Stitching laps of aluminium roofing and cladding sheets
- Stitching of steel and aluminium flashings to roofing and cladding sheets
- Low profile head available powder coated
- Stitching 2 x 0.5mm up to 2 x 1.0mm
- Can be used in conjunction with S12 stainless/EPDM vulcanised sealing washers

Material Specification

- High quality stainless steel grade A2 to ISO 3506, EN 1.4301 to ISO 10088, AISI 304
- · High quality hardened carbon steel drill point






Performance Details

Ultimate Fastener Tensile Strength

Fastener Diameter	kN
4.8* x L	8.40
6.3 x L	15.70




Ultimate Fastener Shear Strength

Fastener Diameter	kN		
4.8* x L	5.40		
6.3 x L	10.20		



Ultimate Pullout Load kN

Fastener Diameter	Nominal Steel Thickness (mm)				Aluminium Thickness (mm)		
	0.60	0.70	0.90	1.20	0.70	0.90	1.20
4.8* x L	0.76	1.02	1.35	2.07	0.73	0.93	1.10
6.3 x L		1.36	2.50	3.26	-	-	-













Self-drilling fastener range

Certifications







*ETA Certification for 4.8 diameter only

Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.

EJOT UK Ltd, Hurricane Close, Sherburn-in-Elmet, Leeds LS25 6PB.

Tel: 01977 687040 Email: info@ejot.co.uk