

OPTICORE JT3-3-5.5 x L range

A2 stainless steel bi-met fastener with engineered integral nylon head for fixing membrane faced sandwich panels to steel sections from 1.2mm - 3.0mm in thickness.

Application Features

- Engineered integral nylon head for rapid coring of the membrane and insulation core for a one step fix of membrane faced sandwich panels
- For steel structures 1.2mm - 3.0mm in thickness

Material Specification


- High quality stainless steel grade A2 to ISO 3506, EN 1.4301 to ISO 10088, AISI 304
- Hardened carbon steel drill point and lead threads
- High impact resistant coloured nylon head. Resistant to temperatures from -40°C to 120°C



Performance Details


Ultimate Fastener Tensile Strength

Fastener Diameter	kN
5.5 x L	11.50




Ultimate Fastener Shear Strength

Fastener Diameter	kN
5.5 x L	7.50



Ultimate Pullout Load kN

Fastener Diameter	Nominal Steel Thickness (mm)					
	1.20	1.40	1.60	1.80	2.50	3.00
5.5 x L	2.10	2.79	3.37	3.98	6.40	7.82





Figures based on tests from construction grade steel designated as S350GD (BS EN 10346), minimum yield strength 350 N/mm².

Ultimate Pullover Load kN

Washer Face	Nominal Steel Thickness (mm)	
	0.63	0.50
Unwashed	5.70	3.50

Figures based on use with Kingspan Topdek profile steel sheets with fastener located in valley of profile.



Drive Tool



Self-drilling fastener range

Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.