

JT6-2-8.0 x 30 range

A4 stainless steel bi-met fastener for stitching roofing and cladding sheets.

Application Features

- For stitching metal to profiled metal sheet or composite panels
- For installing into existing holes for repair purposes replacing smaller diameter stitchers
- Large 8.0mm diameter thread designed to increase stripping torque and provide a secure weather seal

Material Specification

- High quality stainless steel grade A4 to ISO 3506, EN 1.4401 to ISO 10088, AISI 316
- High quality hardened carbon steel drill point



Performance Details

Ultimate Fastener Tensile Strength

Fastener Diameter	kN
8.0 x L	-

Ultimate Fastener Shear Strength

Fastener Diameter	kN
8.0 x L	-

Ultimate Pullout Load kN


Fastener Diameter	Nominal Steel Thickness (mm)			
	0.50	0.70	0.5 x 2	2 x 0.70
8.0 x L	0.97	1.30	1.91	2.45

Figures based on tests from construction grade steel designated as S220GD (BS EN 10346), minimum yield strength 220 N/mm².

Ultimate Pullover Load kN

Washer Face	Nominal Steel Thickness (mm)		
	Steel		
	0.50	0.70	0.90
S16 Washer	3.52	4.62	5.72

Figures based on use with R38 profile steel sheets with fastener located in valley of profile.



Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.