

## JBS-R 7.5 x L range

Case hardened steel fastener for fixing insulation, panels and profiles to concrete.

### Application Features

- Fastener embedment 30mm
- Used in conjunction with the EcoTek tube washer
- T30 Drive
- Requires a 6.0mm diameter pilot hole 40 - 55mm deep
- Installation tool available for tube height adjustment when used in combination with EcoTek

### Material Specification

- Case-hardened steel
- Climadur coated - high-quality coating to improve corrosion protection (15 Kesternich cycles, DIN 50018, 1997)
- High quality case hardened low carbon steel manufactured in accordance with BS EN ISO 10666

### Performance Details


#### Ultimate Fastener Tensile Strength

| Fastener Diameter | kN    |
|-------------------|-------|
| 7.5 x L           | 24.00 |

#### Ultimate Fastener Shear Strength

| Fastener Diameter | kN    |
|-------------------|-------|
| 7.5 x L           | 15.90 |

Onsite tests are recommended to verify performance.



Drive Tool



Self-tapping  
fastener range

Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.