

Case hardened steel fastener light section low profile framing fastener.

Application Features

- For light steel framing connections
- For steel structures with a combined thickness of up to 3.0mm
- Where the minimum head height dimension is required
- P2 drive

Material Specification

- High quality case hardened low carbon steel manufactured in accordance with BS EN ISO 10666
- Organic corrosion resistant finish

Performance Details

Ultimate Fastener Tensile Strength

Fastener Diameter	kN
5.5 x L	14.50





Ultimate Fastener Shear Strength

Fastener Diameter	kN
5.5 x L	9.60

Ultimate Pullout Load kN

Fastener Diameter	Nominal Steel Thickness (mm)						
	1.20	1.40	1.60	1.80	2.00	2.50	3.00
5.5 x L	2.75	3.32	3.89	4.47	5.16	6.45	7.95

Figures based on tests from construction grade steel up to 3.0mm thick designated as S350GD (BS EN 10346), minimum yield strength 350 N/mm².



Drive Tool



Self-drilling fastener range

Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.