

## SF 6.3 x L range

Case hardened steel fastener for fixing roofing or cladding steel sheets side laps and flashings.

### Application Features

- For steel sheets and flashings 0.5mm -1.2mm in thickness
- Can be used in conjunction with A15 and A19 aluminium/EPDM vulcanised sealing washers
- 8mm AF hexagon drive

### Material Specification

- High quality case hardened low carbon steel manufactured in accordance with BS EN ISO 10666
- Organic corrosion resistant finish



### Performance Details

#### Ultimate Fastener Tensile Strength

Fastener Diameter	kN
6.3 x L	17.60

#### Ultimate Fastener Shear Strength

Fastener Diameter	kN
6.3 x L	11.40

#### Ultimate Pullout Load kN






Fastener Diameter	Nominal Steel Thickness (mm)			
	0.50	0.70	0.90	1.20
6.3 x L	1.18	1.36	2.50	3.26

Figures based on tests from construction grade steel designated as S220GD (BS EN 10346), minimum yield strength 220 N/mm<sup>2</sup>.

#### Ultimate Pullover Load kN

Washer Face	Nominal Steel Thickness (mm)			
	0.50	0.70	0.90	1.20
A15 Washer	3.52	4.62	5.72	-
A19 Washer	3.74	5.33	6.91	9.28

Figures based on use with R38 profile steel sheets with fastener located in valley of profile.



Drive Tool

8mm Hex

Self-drilling fastener range

Certifications



Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.