


EJOT Super-SAPHIR® Self-Drilling JT4-6 Range



Ultimate Fastener Tensile Strength



Fastener Dia	kN
5.5 x L	11.5


Material Specification

Fastener.

High quality Stainless steel grade 304 St/St, ISO group A2, Din Werkstoff 1.4301.



Ultimate Fastener Shear Strength



Fastener Dia	kN
5.5 x L	7.5




8mm Hex

Ultimate Pullout Load kN

Fastener Dia	Nominal Aluminium Thickness (mm)				
	2.0	3.0	4.0	6.0	
5.5 x L	2.35	4.60	7.55	8.20	

Figures based on tests from aluminium manufactured in accordance with BS EN 755. Contact EJOT Technical Department for further information on specific grades.

Ultimate Pullover Load kN



Washer Face	Nominal Sheet Thickness (mm)	
	Aluminium	
	0.70	0.90
S16 Washer	2.00	2.20

Figures based on performed in accordance with BS 5427

Figures above are based on results obtained from tests carried out in our Applitec lab in accordance with equipment conforming to BS 5427 on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.

EJOT UK Limited Sherburn-in-Elmet, Leeds LS25 6PB.
Tel: 01977 687040 Fax: 01977 687041
www.ejot.co.uk info@ejot.co.uk