


EJOT SAPHIR® Self-Drilling JT2-18 5.5 Range



Ultimate Fastener Tensile Strength




Fastener Dia	kN
5.5 x L	12.93

Material Specification


High quality grade case hardened carbon steel to Din standard 10666. Organic corrosion resistance finish.




Ultimate Fastener Shear Strength



Fastener Dia	kN
5.5 x L	9.26



Ultimate Pullout Load kN




Fastener Dia	Nominal Steel Thickness (mm)					
	4.0	5.0	6.0	8.0	10.0	12.0
5.5 x L	8.25	10.5	12.93*	-	-	-

* Pullout is limited by the tensile strength of the fastener

Steel 4.0mm and thicker designated as grade S275 (BS EN 10025), minimum yield strength 275Nmm⁻².

Ultimate Pullover Load kN



Washer Face	Nominal Sheet Thickness (mm)			
	0.50	0.70	0.90	1.20
A15 Washer	3.52	4.62	5.72	-
A19 Washer	3.74	5.33	6.91	9.28

Figures for washered fasteners based on use with R32 profile steel sheets with fastener located in valley of profile and tested in accordance with BS 5427.

Figures above are based on results obtained from tests carried out in our Applitec lab in accordance with equipment conforming to BS 5427 on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.

EJOT UK Limited Sherburn-in-Elmet, Leeds LS25 6PB.

Tel: 01977 687040 Fax: 01977 687041

www.ejot.co.uk info@ejot.co.uk

EJOT The Quality Connection