

EJOT Super-SAPHIR® Self-Drilling JT4-2-5.6 x 70



Material Specification

Ultimate Fastener Tensile Strength




Fastener Dia	kN
5.6 x 70	11.70

Fastener


High quality Stainless steel grade 304 St/St, ISO group A2, Din Werkstoff 1.4301.

Ultimate Fastener Shear Strength



Fastener Dia	kN
5.6 x 70	8.80

Ultimate Pullout Load kN



Fastener	35mm soft wood timber rafter
	64mm Embedment
JT4-2-5.6 x 70	6.36kN



8mm Hex



Figures above are based on results obtained from tests carried out in our Appicentre in accordance with equipment conforming to BS 5427 on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.

EJOT UK Limited Sherburn-in-Elmet, Leeds LS25 6PB.
Tel: 01977 687040 Fax: 01977 687041

EJOT Solar i-clip
The single solution
for fixing solar PV frames to UK roofs

- ONE SIZE IS ALL YOU NEED (NO PLAIN DRILL BITS REQUIRED)
- SAVES YOU MONEY (NO EXCESS STOCK REQUIRED)
- SAVES YOU TIME (NO TIME ON SITE)
- APPROVED AND TESTED (TOTAL PEACE OF MIND)
- WIND RESISTANT (UP TO 100 MPH GUSTS)

EJOT The Quality Connection