


# EJOT SAPHIR® Self-Drilling COLORFAST JT2-D-6H Range




## Ultimate Fastener Tensile Strength



Fastener Dia	kN
5.5/6.3 x L	12.50 <sup>†</sup>


## Ultimate Fastener Shear Strength



Fastener Dia	kN
5.5/6.3 x L	8.95 <sup>†</sup>

<sup>†</sup> Ultimate value of low thread shown

## Ultimate Pullout Load kN




Fastener Dia	Nominal Steel Thickness (mm)				
	1.2	1.50	2.00	3.00	6.00
5.5/6.3 x L	2.90	3.44	4.61	8.54	16.29*

\* Pullout is limited by the tensile strength of the fastener

Figures based on tests from steel designated as Grade Z35 (BS 2989), minimum yield strength 350Nmm<sup>-2</sup>.

## Ultimate Pullover Load kN



Washer Face	Nominal Sheet Thickness (mm)		
	0.50	0.70	0.90
CF15 Head	5.10	5.75	6.00
CF19 Head	5.50	6.20	6.50

Figures for washered fasteners based on use with R32 profile steel sheets with fastener located in valley of profile and tested in accordance with BS 5427.

Figures above are based on results obtained from tests carried out in our Applitec lab in accordance with equipment conforming to BS 5427 on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.

EJOT UK Limited Sherburn-in-Elmet, Leeds LS25 6PB.  
Tel: 01977 687040 Fax: 01977 687041  
www.ejot.co.uk info@ejot.co.uk

## Material Specification

### Head.

High impact coloured Nylon head, resistant to temperature from -40°C to 120°C, combined with UV stabilisers to ensure maximum colour retention in outdoor use. Incorporating an EPDM bonded sealing washer.

### Fastener.

High quality grade casehardened carbon steel to Din standard 10666. Organic Corrosion resistance finish

